

Image Format		1/3" Sony Super HAD
Effective Pixels		NTSC : 768(H) X 494(V) PAL : 752(H) X 582(V)
H.Resolution		500 TV Lines
Min. Illumination		0.2Lux / F2.0
Power source		12VDC / 130mA or less
Special	True Day/Night	O
IP Rating		IP68
Synchronizing system		Internal
Scanning system		NTSC 525 Lines PAL 625 Lines 2:1 Interlaced
Video output		1.0Vp-p Composite. 75 Ohms
S/N ratio		More than 50dB (AGC Off)
Shutter Speed		NTSC : 1/60~1/100,000 sec PAL : 1/50~100,000 sec
Gamma correction		r=0.45
White Balance		2100°K ~ 9100°K Auto
Gain Control		4dB~30dB Auto
Smear Effect		0.005%
MTBF		80,000 hours
Lens	Standard	f=4.3mm (78°)
	Option	3.6 / 4.3 / 6.0 / 8.0 / 12 / 16mm
Operating Temperature		14°F ~ 122°F (-10°C ~ +50°C)
Humidity		Within 90% RH
Output Terminal		4 Feet DIY cable with BNC-Female for Video, 2.1mm DC-Jack for Power
Measurement (mm)		21mm(Dia) x 78mm(L)
Weight (Approx.g)		165
Optional True Features	External Audio	O