

Image Format	1/3" CCD, Sharp-High res	
Effective Pixels	NTSC : 768(H) X 494(V) PAL : 752(H) X 582(V)	
H.Resolution	480 TV Lines	
Power source	12VDC / 80mA or less	
Synchronizing system	Internal	
Scanning system	NTSC 525 Lines NTSC 625 Lines 2:1 Interlaced	
Video output	1.0Vp-p Composite. 75 Ohms	
S/N ratio	More than 50dB (AGC Off)	
Shutter Speed	NTSC : 1/60~1/100,000 sec PAL : 1/50~100,000 sec	
Gamma correction	r=0.45	
White Balance	2100°K ~ 9100°K Auto	
Gain Control	4dB~30dB Auto	
Smear Effect	0.005%	
MTBF	80,000 hours	
Lens	Standard	f=3.6mm (92°)
	Option	2.9 / 4.3 / 6.0 / 8.0 / 12 / 16mm
Operating Temperature	14°F ~ 122°F (-10°C ~ +50°C)	
Humidity	Within 90% RH	
Output Terminal	4 Feet DIY cable with BNC-Female for Video, 2.1mm DC-Jack for Power	
Measurement (mm)	30mm x 30mm(28mm x 28mm)	
Weight (Approx.g)	90	
Optional Features	Internal Audio	O
	External Audio	O